

# MIMO

## Product Sheet

MIMO is a true demountable glass partition system offered in single and double glazing within the same extrusion. The line is exceptionally versatile and can accommodate any architectural needs including transoms and clerestories, almost limitless ceiling heights, solid panels, freestanding partitions, and a wealth of door types including framed and frameless swing and sliding, as well as a unique pocket sliding door.



## Extrusions



## Glazing and Panels:

- Single and double glazing
- Thickness: ½" and ¾"
- Tempered, laminated, low iron (extra clear), and speciality glass
- Solid panels

## Gaskets:

- Door: available in black, white, and clear
- Wall: available in black, white, and grey

## Integrated electrical components:

- High and low voltage wiring
- Integrated electrical components including room scheduler, card reader, and electrical strike available
- Panic hardware available

## Lead times:

- Black Anodized, Clear Anodized, and Powder Coats: 6-8 weeks
- Specialty and custom: finishes, glass, hardware etc.: +8 weeks

## Tolerance:

- Total of 1-¼"

## Ceiling Condition:

- Can be installed on a bulk ceiling, acoustical tiles (ACT), or as a free-standing system
- Maximum height of 10'
- 20'+ with clerestory and transom available

## Doors:

### Frameless

- Single glazed sliding door
- Single glazed hinged door
- Single glazed pivot door

### Framed

- Standard Muraflex single glazed pivot door
- Standard Muraflex double glazed pivot door

### Wood

- Hinge door
- Pivot door

### Standard door hardware

- Lever or ladder pull
- Locking or non-locking
- Drop seal available on framed and wood doors
- Hold open available on all swing doors

Maximum door height: 10'

## Junctions:

- Available in aluminum and polycarbonate
- Glass to glass, corner (L), and T condition

## Acoustical properties:

- Single glazed tested STC assembly score ranges (depending on options): 34 - 38
- Double glazed tested STC assembly score ranges (depending on options): 43 - 45

## Profile:

Stick built

### Profile dimensions:

- Top and bottom extrusion: W 3" x H1-9/16"
- Sliding single or double glazed door adds W15/16"
- Same extrusion for centered, offset, and double glazing

### Aluminum

- Applied and integrated mullions available
- Aluminum and wood flyby available

# MIMO

## Sustainability & Finishes



### Sustainability


At Muraflex, we are dedicated to diminishing our impact on the environment. We are also committed to continually improving our procedures in terms of product development, supply, packaging and distribution in an effort to minimize our environmental footprint.



Declare.



### The Finishes



Due to variances in screen calibration or print quality, finish images may not accurately represent the actual color sample.